

## White soft PVC hose with hard PVC spiral.

Suitable for delivery of condensed water.



**Flexibility**



**Crushing**



**Abrasion resistance**



**Chemical resistance**

Chemical Resistance Chart

**Temperature range**

-5°C +60°C



Agriculture



Industry



Home



Building



Food & beverage

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Workpress bar	Burstpress bar	Vacuum mH2O	Coillenght mt	Pallet mt	Dimension pallet cm
587G0020	5/8"	16	20,3	85	16	-	-	-	50	2500	80x120
587G0030		18	22,3	90	18	-	-	-	50	2500	80x120
587G0040		20	24,3	95	20	-	-	-	50	2500	80x120
587G0050	1"	25	30,0	140	25	-	-	-	50	1200	80x120

NOTES:  
 CHEMICAL RESISTANCE CHART available on TP REFLEX web site.  
 TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.  
 DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.  
 TOLERANCE: from 12 mm to 20 mm: ± 0.3 mm | from 22 mm to 50 mm: ± 0.5 mm | from 51 mm to 100 mm: ± 1.0 mm | from 102 mm to 150 mm: ± 1.5 mm from 152 mm to 200 mm: ± 2.0 mm other values: ±5%  
 TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.  
 TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.