

Trasparent soft PVC hose with red hard PVC spiral.

Suitable for delivery and suction of food liquids, wines and alcoholic liquids.



Flexibility



Crushing resistance



Abrasion resistance



Chemical resistance

Chemical Resistance Chart

Temperature range

-5°C +60°C



Agriculture



Industry



Home



Building



Food & beverage

Suitable for contact with food and food liquids Simulant A.B.C and alcoholic liquids up to 20% in compliance with Regulation (EC) No. 1935/2004, Regulation (EC) No. 2023/2006 and Regulation (EU) No. 10/2011 and its successive amendments.



Phthalate FREE. 

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Workpress bar	Burst press bar	Vacuum mH2O	Coil length mt	Pallet mt	Dimension pallet cm
587I0630		20	27,5	300	100	8	24	8	50	1200	80x120
587I0640	1"	25	33,0	400	125	8	24	8	50	1200	80x120
587I0650		30	39,0	500	150	7	21	8	50	1000	80x120
587I0660	1 1/4"	32	41,0	550	160	7	21	8	50	1000	80x120
587I0670		35	44,5	600	175	7	21	8	50	500	80x120
587I0680	1 1/2"	38	48,0	680	190	7	21	8	50	300	80x120
587I0690		40	50,0	750	200	7	21	8	50	300	80x120
587I0700	1 3/4"	45	55,0	900	225	7	21	8	50	300	80x120
587I0710		50	60,5	1100	250	7	21	8	50	300	80x120
587I0720		60	71,0	1450	300	6	18	8	50	250	110x130
587I0730	2 1/2"	63	74,0	1550	315	6	12	8	50	250	110x130
587I0740		70	82,0	1800	350	6	12	8	50	250	110x130
587I0750	3"	75	88,0	1900	375	6	12	8	50	250	110x130
587I0760		80	95,0	2200	400	6	12	8	30	180	110x130
587I0770	3 1/2"	90	105,0	2560	450	6	12	8	30	150	110x130
587I0780		100	117,0	3300	500	6	12	8	30	150	110x130
587I0790	4"	102	119,0	3400	510	6	12	8	30	150	110x130
587I0800		110	127,5	3800	550	3	9	8	30	150	110x130
587I0810		120	138,0	4300	720	3	9	8	30	120	110x130
587I0820		125	143,5	4500	750	3	9	8	30	100	110x130
587I0830	5"	127	145,5	4600	762	3	9	8	30	100	110x130
587I0840		150	171,5	6600	1050	3	9	8	20	80	110x130
587I0850	6"	152	173,5	6700	1064	3	9	8	20	80	110x130
587I0860		200	224,0	10300	1600	-	-	0	20	60	110x130

NOTES:
 CHEMICAL RESISTANCE CHART available on TP REFLEX web site.
 TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.
 DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.
 TOLERANCE: from 12 mm to 20 mm: ± 0.3 mm | from 22 mm to 50 mm: ± 0.5 mm | from 51 mm to 100 mm: ± 1.0 mm | from 102 mm to 150 mm: ± 1.5 mm from 152 mm to 200 mm: ± 2.0 mm other values: ±5%

TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.

TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.