

## Soft PVC hose with Polyester yarn reinforcement.

Suitable for transporting industrial liquids and compressed air.



**Flexibility**



**Crushing resistance**



**Abrasion resistance**



**Chemical resistance**

Chemical Resistance Chart

**Temperature range**

-5°C +60°C



Agriculture



Industry



Home



Building



Food &  
beverage

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Workpress bar	Burstpress bar	Vacuum mH2O	Coillenght mt	Pallet mt	Dimension pallet cm
595A2350	3/16"	5	10,5	115	-	20	60	-	100	3000	80x120
595A2360	1/4"	6	14	185	-	20	60	-	100	3000	80x120
595A2370	5/16"	8	17	265	-	20	60	-	100	3000	80x120
595A2380		10	19	305	-	20	60	-	100	2000	80x120
595A2390	1/2"	13	23	415	-	20	60	-	100	2000	80x120
595A2400	5/8"	16	26	490	-	20	60	-	100	1000	80x120

### NOTES:

CHEMICAL RESISTANCE CHART available on TP REFLEX web site.

TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.

DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.

TOLERANCE: from 5 mm to 12 mm: ± 0.3 mm | from 13 mm to 19 mm: ± 0.5 mm | from 20 mm to 40 mm: ± 0.8 | other values +- 5%

TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.

TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.