

Grey soft PVC hose with hard PVC spiral.

Suitable for suction and delivery of air, fumes, dusts and ventilation
Self Extinguishing Raw Materials at least V2 UL94 (th 1,6 mm).



Flexibility



Crushing



Abrasion resistance



Chemical resistance

Chemical Resistance Chart

Temperature range

-5°C +60°C



Agriculture



Industry



Home



Building



Food & beverage

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Work press bar	Burst press bar	Vacuum mH2O	Coillenght mt	Pallet mt	Dimension pallet cm
587C1980		12	16,0	80	12	-	-	5	50	3000	80x120
587C1990	1\2"	13	17,0	82	13	-	-	5	50	3000	80x120
587C2000		14	18,5	85	14	-	-	5	50	3000	80x120
587C2010	5\8"	16	20,5	90	16	-	-	5	50	3000	80x120
587C2020	3\4"	19	23,5	95	19	-	-	5	50	2500	80x120
587C2030		20	24,5	100	20	-	-	5	50	2500	80x120
587C2040	7\8"	22	27,0	120	22	-	-	5	50	2000	80x120
587C2050	1"	25	30,0	140	25	-	-	5	50	1200	80x120
587C2060		30	35,5	200	30	-	-	5	50	1000	80x120
587C2070	1 1\4"	32	37,5	215	32	-	-	5	50	1000	80x120
587C2080		35	40,5	240	35	-	-	5	50	500	80x120
587C2090	1 1\2"	38	43,5	265	38	-	-	5	50	300	80x120
587C2100		40	45,5	280	40	-	-	5	50	300	80x120
587C2110	1 3\4"	45	51,0	360	45	-	-	5	50	300	80x120
587C2120		50	57,5	450	50	-	-	5	50	300	80x120
587C2130		55	62,5	490	55	-	-	5	50	300	110x130
587C2140		60	68,0	540	60	-	-	5	50	250	110x130
587C2150	2 1\2"	63	71,0	560	63	-	-	5	50	250	110x130
587C2160		65	73,0	590	65	-	-	5	50	250	110x130
587C2170		70	78,5	640	70	-	-	5	50	250	110x130
587C2180	3"	76	84,5	720	76	-	-	5	50	250	110x130
587C2190		80	89,0	780	80	-	-	5	50	180	110x130
587C2200	3 1\2"	90	99,0	830	90	-	-	5	50	180	110x130
587C2210		100	110,0	980	100	-	-	5	30	180	110x130
587C2220	4"	102	112,0	1000	102	-	-	5	30	180	110x130
587C2230		110	120,5	1050	110	-	-	4	30	180	110x130
587C2240		120	130,5	1200	120	-	-	4	30	180	110x130
587C2250		125	135,5	1250	125	-	-	4	30	120	110x130
587C2260	5"	127	137,5	1275	127	-	-	4	30	120	110x130
587C2270		130	141,0	1300	130	-	-	4	30	120	110x130
587C2280		140	151,0	1500	140	-	-	4	30	120	110x130
587C2290		150	161,5	1700	150	-	-	4	20	100	110x130
587C2300	6"	152	163,5	1750	152	-	-	4	20	100	110x130
587C2310		160	172,5	1900	160	-	-	4	20	80	110x130
587C2320		180	193,0	2200	180	-	-	4	20	60	110x130
587C2330		200	214,0	2400	200	-	-	4	20	60	110x130

NOTES:

CHEMICAL RESISTANCE CHART available on TP REFLEX web site.

TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.

DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.

TOLERANCE: from 12 mm to 20 mm: ± 0.3 mm | from 22 mm to 50 mm: ± 0.5 mm | from 51 mm to 100 mm: ± 1.0 mm | from 102 mm to 150 mm: ± 1.5 mm from 152 mm to 200 mm: ± 2.0 mm other values: ±5%

TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.

TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.