

soft PVC hose under layer in special material with hard PVC spiral.

Suitable for supply of water in swimming pool and spa



Flexibility



Crushing resistance



Abrasion resistance



Chemical resistance

Chemical Resistance Chart

Temperature range

-5°C +60°C



Agriculture



Industry



Home



Building



Food &
Beverage

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Workpress bar	Burst press bar	Vacuum mH2O	Coil lenght mt	Pallet mt	Dimension pallet cm
587P0300		42	50	790	295	5	15	8	50	250	80x120
587P0310		43	50	700	300	5	15	8	30	240	80x120
587P0320		55	63	990	385	4	12	8	30	210	110x130

NOTES:

CHEMICAL RESISTANCE CHART available on TP REFLEX web site.

TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.

DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.

TOLERANCE: from 12 mm to 20 mm: ± 0.3 mm | from 22 mm to 50 mm: ± 0.5 mm | from 51 mm to 100 mm: ± 1.0 mm | from 102 mm to 150 mm: ± 1.5 mm from 152 mm to 200 mm: ± 2.0 mm other values: ±5%

TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.

TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.